



Features

- Can be recessed or surface mounted
- Ultra low recessed profile design
- Made of lightweight high quality aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable extrusion and lenses
- Optional end caps and mounting clips available
- Compatible with most Trulux Tape Light

Available Lengths

39-3/8" (1 meter)

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT (excludes Double Row)
- Trulux RGB

TRULUX™ Universal Mini Extrusion

The low profile Universal Mini is a short version of the Universal and needs only a 1/4" depth if recessed. Use the frosted UV resistant/flame retardant lens, made of high quality polycarbonate material. End caps make a finished look. E-CLIPS are recommended for most surface applications, especially when mounted to the underside of a shelf or cabinet.

Best suited applications:

Stairs, handrails, display shelving and cases, niche and accent lighting

Ordering Information

PE-AA1-1M	Universal Mini Aluminum Extrusion
PE-UVLENS-1M	Frosted Polycarbonate UV Lens
PE-FOCLENS-1M	Beam Angle Focusing Lens (60° with Mini Universal)
PE-AA1-END	Mini End Cap
E-CLIP	Surface Mount Clip

